DYNAMICS OF MACHINERY

Published @ 2017 Trieste Publishing Pty Ltd

ISBN 9780649566242

Dynamics of Machinery by Gaetano Lanza

Except for use in any review, the reproduction or utilisation of this work in whole or in part in any form by any electronic, mechanical or other means, now known or hereafter invented, including xerography, photocopying and recording, or in any information storage or retrieval system, is forbidden without the permission of the publisher, Trieste Publishing Pty Ltd, PO Box 1576 Collingwood, Victoria 3066 Australia.

All rights reserved.

Edited by Trieste Publishing Pty Ltd. Cover @ 2017

This book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form or binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser.

www.triestepublishing.com

GAETANO LANZA

DYNAMICS OF MACHINERY

Trieste

DYNAMICS OF MACHINERY

BY

GAETANO LANZA, S.B., C. & M.E. Emgineer; Professor Emeritor of Technicial and Applied Mechanics Massachurers Institute of Technology

> FIRST EDITION FIRST THOUSAND

UNIV. OF CALIFORNIA

NEW YORK JOHN WILEY & SONS London: CHAPMAN & HALL, Limited 1911

- 69

14

E

1317) 1317)

Copyright, 1911, by GABTANO LANZA

UMIV, OF CALFORNIA

> Stanbore Press P. H. GILBON COMPANT BORTON, U.S.A.

> > · · · ·

PREFACE

WHILE Chapter I treats of the principal types of Dynamometers, the remainder of this book has for its chief object to bring together, in one volume, the methods of dealing with the inertia forces that arise in various kinds of machinery especially in cases where high speeds are employed. As examples, may be cited those of highspeed steam engines, including high-speed locomotives, and of gas engines.

In these, careful consideration must be given to the action of the reciprocating parts, not only for the purpose of balancing, and hence avoiding undue strains in the machine itself, or in the foundations, and undue distortions in the rails, but also in order that the parts of the engine, including the crank shaft, etc., may be properly designed to resist the stresses to which they are subjected.

Other examples in which the inertia forces must be given careful consideration are: the inertia governor, — inasmuch as these forces affect very considerably the regulation, — pulleys, flywheels, steam turbines, dynamo armatures, centrifugal machines, hydroextractors, etc., which should be in running as well as in standing balance.

Another set of examples includes those in which the gyroscope is employed in engineering, as (a) the steering of torpedoes, (b) the steadying of vessels at sea, (c) the Brennan monorail car, (d) the gyroscopic compass, etc.

iii

258676

.

.

5 5

ž

1.2 1.2

TABLE OF CONTENTS

145

Снартия	PAGE
I. DYNAMOMETERS	1
II. MOMENTS AND PRODUCTS OF INDERTA	20
III. ACTION OF RECIPROCATING PARTS.	33
IV. Governors	135
V. BODIES BAVING & HIGH ROTATIVE SPEED	200
Appendix to Chapter II (A)	223
APPENDIX TO CHAPTER IV (B)	232
APPENDIX TO CHAPTER V (C)	238

83

a a

(j) 21

6 6 13

()

- UMIV., OF California

DYNAMICS OF MACHINERY

CHAPTER I.

DYNAMOMETERS.

DYNAMOMETERS, as their name implies, are instruments for measuring power.

They may be divided into two main classes, viz., traction dynamometers and rotation dynamometers. The first are intended to measure the work done by a direct pull or thrust; as, for instance, the work done by a locomotive in drawing a train, or that required to towa boat. Rotation dynamometers, on the other hand, are intended to measure the power transmitted to or through a rotating shaft.

Traction dynamometers are all practically some kind of a weighing device, the main part of which consists of a spring, or of a hydraulic cylinder and piston, by means of which the pull exerted is weighed, together with some device for measuring the speed of motion.

When the pull and the speed are both constant, it is only necessary to multiply them together to obtain the work done per unit of time. On the other hand, when one or both vary, it becomes necessary to have recourse to some kind of a recording apparatus, and then to obtain the area of the resulting irregular figure by means of a planimeter or otherwise.

Dynamometer Cars.

Many of the large railroads make use of a dynamometer car, principally for the purpose of obtaining a tonnage rating, for the different parts of the service; determining the amount of energy, the draw-bar pull, and the power, and hence the kind of locomotive required to perform the service.

In all these cases, the force with which the portion of the train behind the dynamometer car pulls upon the drawbar of the latter is weighed, and recorded upon a strip of paper, which is caused by suitable mechanism to travel at a speed proportional to that of the train.

We thus obtain a diagram (see Fig. 1) in which the abscissæ represent to scale distances travelled by the train along the road, while the ordinates represent to scale the draw-bar pull exerted at

ι.

Copyright, 1911, by GAETANO LANZA.