# IGNITION DEVICES FOR MOTORS WITH A CHAPTER TREATING SPECIALLY OF STRUCTURAL DETAILS, CHOICE, AND MANAGEMENT OF AUTOMOBILES

Published @ 2017 Trieste Publishing Pty Ltd

### ISBN 9780649482320

Ignition Devices for Motors with a Chapter Treating Specially of Structural Details, Choice, and Management of Automobiles by S. R. Bottone

Except for use in any review, the reproduction or utilisation of this work in whole or in part in any form by any electronic, mechanical or other means, now known or hereafter invented, including xerography, photocopying and recording, or in any information storage or retrieval system, is forbidden without the permission of the publisher, Trieste Publishing Pty Ltd, PO Box 1576 Collingwood, Victoria 3066 Australia.

All rights reserved.

Edited by Trieste Publishing Pty Ltd. Cover @ 2017

This book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form or binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser.

www.triestepublishing.com

# S. R. BOTTONE

# IGNITION DEVICES FOR MOTORS WITH A CHAPTER TREATING SPECIALLY OF STRUCTURAL DETAILS, CHOICE, AND MANAGEMENT OF AUTOMOBILES



### Net Book.

**C.** This book is supplied to the trade on terms which do not allow them to give a discount to the public.

# IGNITION DEVICES

FOR

## **MOTORS**

### WITH A CHAPTER .

TREATING SPECIALLY OF

STRUCTURAL DETAILS, CHOICE, AND MANAGEMENT OF AUTOMOBILES

## By S. R. BOTTONE

AUTHOR OF "AMATEUR ELECTRICIAN'S WORKSHOP," "TALKING MACHINES & RECORDS," "ELECTRICAL ENGINEERING FOR STUDENTS," "MODERN DYNAMOS & BATTERIES

NEW EDITION, THOROUGHLY REVISED AND ENLARGED

Bully Blustrateb

GUILBERT PITMAN 85, FLEET STREET, LONDON, E.C.

[All rights reserved



### ILLUSTRATIONS.

							P	VCR.
Fig.	t.	Section of Engine, fr	ront v	iew	***	110	200	12
22	2.	,, ,, S	ide vi	ew	***	560	***	13
**	34.	Carburetter, elevation	n	***	0.00	***	***	16
22	3B.	" section	003	200	233	632	(0.00)	17
**	4-	"Lantern" Mixing	Valve	(exe		***	***	19
22	5.	Simple Clutch	***	***		***	333	20
22	6.	De Dion Clutch	600	2000	200	***	22.5	20
25	7.	Darracq Gear Box	***	446		***	****	21
**	8.	De Dion "	***	***	(***)	***		22
**	9.	Plan of Chassis		0.66	1895	144	244	24
**	10.	Chassis as seen from	n belo	w	0.00	***	100.00	25
33	11.	Differential Gear	200	225	6000	2230		27
19	12.	Darracq Steering G	ear	2222	eess	2000		28
33	13.	Front View of Car	***	12.55	2000	2000	1906	30
"	14.	Single Cylinder Mo	tor	***	Itte:	31050	2555	31
27	15.	Simple Silencer	200	***	***	***	****	32
77	16.	Universal Silencer	355	2555	6960	***	1222	33
111	17.	Parson's Petroleum	Engir	ю		2500	22.55	43
"	18.		. 11	sho	wing V	alves		46
***	19.	н н	- 11		. 29		***	47
13	20.	Conventional diagra	ım of	Armat		2744		59
	21.	H or Shuttle Armat	ure	***				60
	22.	Simms' 1900 Motor	with !	Magne	10	***	•••	62
	23.	The Bassée Michel	Magn	eto		***		63
	24.	The Dynamo Coil	•••		***	***		67
	25.	27 23				•••		68
	26.	2 72				1.0		60

### ILLUSTRATIONS.

							- 2	1000000
Fig	27.	The Eisemann A	rmature	5		10000		AGE 70
								337
**	28.	,, p	lagneto	***	***		***	71
33	29.	77	33	***	***	***		73
22	30,	**	11	***		444	***	74
,,	31,	31	**	***	***	***	***	75
19	32.	,,	**		***	***	***	76
**	33-	39	**	(wiring)			•••	77
,,	34-	19	95	***	***	***	•••	78
"	35-	***	17	60	***	***	***	79
35	36.	Sparking Plug	441	366	•••	***	***	80
>>	37.	Simms-Bosch A	rc-Ligh	t Magnet	0	***	***	81
33	38.	The Gianoli Ma	gneto	***		***		84
22	39.	33	17	•••	***	•••	***	85
12	40.	31	11	***	***	***	***	86
,,	41.	" Timing" the	Spark	3939	22	***	•••	97
"	42.	Major Torren's	" Prima	ry Coil"	Spari	king Pl	ug	102
11	43.	Diagrammatic S	Section	of Second	dary (	Coil	***	105
**	44.	Contact Breake	r	1944	*9*		1.44	122
	45.	Connection of C	Coil with	Tremble	er	***		127
11	46.							131



### CHAPTER I.

### CHOICE AND MANAGEMENT OF AUTOMOBILES.

OTOR cars, tri-cars, and motor bicycles present so much matter of interest, and are entering so largely into our every-day life, that every one should have some knowledge of the principles of their construction. This knowledge, even though it be elementary, is absolutely necessary to the would-be purchaser, otherwise he may be led astray in the choice of a car by its outward appearance, instead of directing his attention to those essentials on which the proper working and convenience of manipulation depend. Although . modifications and improvements are being continually introduced, yet the main features of the propelling arrangements adopted by nearly all automobile manufacturers are based on the practice of the leading makers in France, where, owing to the freedom from irksome restrictions on the road, the art of constructing and working light, powerful motors, actuated by petrol, alcohol, steam, or electricity, has reached a higher level of perfection than perhaps in any other country.

The first essential in an automobile is the power of travelling, and this power it obtains from the engine. The type of motor now almost universally adopted for the propulsion of automobiles is a modification of that known as the "internal combustion engine." In this the power is derived from the explosion of a mixture of air and petrol vapour confined in the upper portion of a cylinder, in which travels a piston, connected by a crank to a fly-wheel, and other accessories. Petrol is an extremely volatile spirit (a hydro-carbon), obtained from petroleum by distilla-Being so volatile, it evaporates readily, and forms with air a gaseous mixture, which can readily be ignited by the electric spark. On being thus fired, it explodes, great heat and consequent expansion occurring at the same time. allowing ignition to take place, the gaseous mixture be compressed, the force of the explosion is much exalted-hence, greater power is obtainable from the explosion. For this reason, in all modern gas and petrol engines, great attention is paid to obtaining a proper amount of compression before firing the mixture. The explosion is made to take place by means of a "timed" electric spark when the compression of the gaseous mixture has reached a certain predetermined point.

We reproduce two outline illustrations of a typical petrol motor (Figs. 1 and 2), in order to enable the reader to follow out the principle on which such engines act, and this principle remains the same in all, although modifications are to be found in the constructional detail of the engines turned out by the various makers. We may here mention that the flywheel which is shown at the back of the lower portion of Fig. 1, and to the right of Fig. 2, is usually outside the case of the engine itself; but in some of the smaller motors of the cycle pattern, it is itself

enclosed, the spindle alone projecting. Fig. 1 is a front section, and Fig. 2 a side view, of the ordinary petrol motor-in which 1 is the cylinder, 2 the cylinder cover, and 3 the chamber containing the crank. This chamber is fitted with two covers, 4 and 5, the latter of which has on it a box, 6, whence arises a stud, 7, carrying a sleeve, 8, whereon is formed the exhaust-valve cam. To this sleeve is keved the gear-wheel, o, which is driven by a pinion, 10, fastened to the crank-shaft, 11. Since the number of teeth on the gear-wheel, o, is twice that of those on the pinion, 10, it revolves at half the speed of the crank-shaft, thus operating the exhaust-valve at every alternate in-stroke of the piston. At 12 is the piston, which is furnished with three metal rings, 13, which enable it to make a gas-tight fit in the cylinder; and 14 is the connecting-rod, fitted with brasses at The valve-box, 15, is cast on the side of the cylinder, and communicates with the combustion chamber, 16, by the port. The valve-box has a waterjacket in communication with the water-jacket, 29, 30, of the cylinder, which device prevents the valveseatings becoming unduly heated. At 17 is an inletvalve which is automatic in its action, opening by the suction of the piston, against the light spring, 18. A stronger spring, 20, controls the exhaust-valve, 19, which therefore resists the suction stroke, but is lifted from its seat at every second revolution of the engine by the cam on the sleeve, 8. This cam raises the roller, 21, on the bell-crank lever, 22, pivoted at 23, the other end of the bell-crank lever having the push-rod, 24, jointed to it. This rod serves to lift up the exhaustrod at the right times. The gear-wheel, 9, is made