# VALVE-GEARS

Published @ 2017 Trieste Publishing Pty Ltd

ISBN 9780649728411

Valve-Gears by H. W. Spangler

Except for use in any review, the reproduction or utilisation of this work in whole or in part in any form by any electronic, mechanical or other means, now known or hereafter invented, including xerography, photocopying and recording, or in any information storage or retrieval system, is forbidden without the permission of the publisher, Trieste Publishing Pty Ltd, PO Box 1576 Collingwood, Victoria 3066 Australia.

All rights reserved.

Edited by Trieste Publishing Pty Ltd. Cover @ 2017

This book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form or binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser.

www.triestepublishing.com

H. W. SPANGLER

# **VALVE-GEARS**

Trieste

C. Annive

### VALVE-GEARS.

Ľ

ł.

28

BY H: WP SPANGLER, Whitney Professor of Muchankal Engineering in the University of Pennylvenia.

Analysis by the Zeuner Diagram.

ONE HUNDRED AND NINE ILLUSTRATIONS.

SECOND EDITION, REVISED AND ENLARGED.

SECOND THOUSAND.

×.

NEW YORK; JOHN WILEY & SONS. LONDON; CHAPMAN & HALL, LTD.

1898.

COPVEIGHT, 1890, SY H. W. SPANGLER,

13

<u>a</u>

٠

1

144

10 18

39

.

32

् स् या स्टब्स् या स्टब्स्

ROBERT DRUMMOND, ELECTROTYPER AND PRINTER, NEW YORK,

Engin Mr From the Library of Rof. C.S. Denison 7-2-21

#### PREFACE.

THE writer, needing a book for class use which would give in one volume those parts of the theory of valve-gears necessary to a clear understanding of the subject, has prepared the following work.

All the standard text-books on the subject, the current periodicals, and working drawings have been called on for data and methods, and the works of Zeuner, Auchincloss, Rankine, Whitham, Halsey, Marks, Reuleaux, Bilgram, and the files of *Engineering* and the *Engineer* have been freely used in preparing the text; but the matter has been put in its present shape by the author.

A few of the methods are original, but others confronted with the same problems have probably solved them in the same or in a better way.

The designing of valve-gears is entirely a drawing-board process; and in all but radial gears, and to a great extent even there, the actual method of laying down the work is given.

The mathematical proof of the methods and results used is given whenever possible.

The problems are in most cases made up from the data of engines actually in use.

H. W. SPANGLER.

UNIVERSITY OF PRNNSYLVANIA,

PHILADELPHIA, PA., August 20, 1890.

....

÷

r

đ

64 80 

### CONTENTS.

5.455

• • •

1 1 1

25

13

#### CHAPTER I.

#### PLAIN SLIDZ-VALVES,

| x.  | Plain slide-valves,   | 3005       | •           |         |       | 20    |        | 3 <b>4</b> 3 |     | •            |    | I. |
|-----|-----------------------|------------|-------------|---------|-------|-------|--------|--------------|-----|--------------|----|----|
| 3.  | Method of action of v | alve       |             |         | ÷.    |       |        |              |     |              |    | 2- |
| 3.  | The eccentric, .      |            | 22          | 1       | ÷.    | 12    | 1.     |              |     | 8            |    | 2. |
| 4.  | Valve seat, face, and | ports      | 3, .        | 10      |       |       | ÷.     |              | •   |              |    | 3  |
| 5.  | Lap,                  | -          |             | 86      |       |       |        |              | •   |              | 39 | 4  |
| 6.  | To determine positio  | a of       | valve       | and     | pisto | n,    |        |              | •   |              |    | 4  |
| 7.  | Distance valve has m  | oved       | fron        | 1 its e | entre | l pos | ition, |              |     |              |    | 5  |
| 8,  | Yoke-connection,      | 3 <b>9</b> | <b>6</b> 36 |         |       |       | 219    | 3 <b>9</b> 1 | •   | $\mathbf{x}$ |    | 5  |
| 9.  | Valve-diagrams, .     | 4          |             |         |       |       |        |              | •   |              |    | 6- |
| 10. | Angle between crank   | and        | CCCCD       | tric 9  | ю",   | 12    | 34     |              | - E | ÷.           |    | 7  |

#### CHAPTER II.

#### THE ZEUNER DIAGRAM

| 11. | To draw th  | ne va | lve-di        | agra | m,    | 23          |     |     | 82 | 10    |   |   |  | 10  |
|-----|---|-------|---------------|------|-------|-------------|-----|-----|----|-------|---|---|--|-----|
| 12, | Point of an   | Imise | sion,         | 8    |       | <b>8</b> 02 |     | 300 |    |       |   | ٠ |  | 10  |
| 13. | Angular as  | dvane | ce,           | 18   | 0.000 | •           |     |     | 18 | 0.000 | • |   |  | IL  |
| 14. | Lead, .   |       |               |      |       | 1           | 12, |     |    |       |   |   |  |     |
| 15. | 5. From a given engine to draw the diagram,         |       |               |      |       |             |     |     |    |       |   |   |  | 13  |
| 16. | Distributio   | am,   | 5 <b>9</b> 00 | •    | ٠     |             | 14  |     |    |       |   |   |  |     |
| 17. | . Separate diagrams for each end of the cylinder, . |       |               |      |       |             |     |     |    |       |   | ٠ |  | 34. |

#### CHAPTER III.

#### OVERTRAVEL AND PROBLEMS.

| 18, | Overtravel, | •    | ×     | . A    | .885   | . 8.   | . ×.  | . X.,  | 38      |     |            |   | 19  |
|-----|-------------|------|-------|--------|--------|--------|-------|--------|---------|-----|------------|---|-----|
| 19. | Problem I,  | give | 1 7,  | d, cut | -off a | nd er  | khaus | t clos | nare,   | 300 | <b>9</b> 7 |   | 19  |
|     | Problem 2,  | give | n lag | , ext  | aust   | lap, l | cad a | nd cu  | ut-off, |     | •          |   | 20. |
|     |             |      |       |        |        |        |       |        |         |     |            | v |     |

#### CONTENTS.

| 21. | Problem 3, given cut-off, angle of lead, port and ov | ertra | rel,    | 12                   | 21     |
|-----|--|-------|---------|----------------------|--------|
| 22. | Problem 4, given cut-off, lead and port-opening,     |       |         | 3                    | <br>22 |
| 23. | When the piston and eccentric rods do not travel or  | para  | llel li | ines,                | 23     |
| 24. | To determine the position of the eccentric,          |       |         | 20040<br>20 <b>4</b> | 24     |
| 25. | Effect of changing dimensions,                       |       | 26      | 24                   | <br>25 |

#### CHAPTER IV.

.

#### MODIFICATIONS OF THE PLAIN SLIDE-VALVE.

| 26.   | Double-ported valves  | ŔĊ. | 1   |     | 0. | 156  |              | 28  |    | 1913 | 28 |
|-------|-----------------------|-----|-----|-----|----|------|--------------|-----|----|------|----|
| 27.   | Allen or Trick valve, |     |     |     |    |      |              | S., |    |      | 28 |
| 28.   | Piston-valves, .      |     | ) š | - 2 | 2  | 1    |              |     |    |      | 30 |
| 29.   | Taking steam inside,  | 1.  |     |     |    | 16   |              | 1   |    | 8.0  | 30 |
| . 30. | Two or more valves,   | ۰,  | e   |     |    | 0.00 | 3 <b>•</b> 3 |     | 20 |      | 31 |

#### CHAPTER V.

#### EQUALIZING CUT-OFF, LEAD, COMPRESSION, AND RELEASE.

| 31. | Equalizing cut-off,    | •    | 10 T     | 100   | 3.9    | 1005   |      |    |          |     | 34 |
|-----|------------------------|------|----------|-------|--------|--------|------|----|----------|-----|----|
| 32. | Equalizing cut-off and | lead | l, ,     |       |        |        | •    |    |          |     | 35 |
| 33. | Equalizing exhaust an  | d co | mpressio | n, .  |        |        |      |    |          | 111 | 36 |
| 34. | Circular diagram for   | lete | mining r | noven | aent e | aig lo | ton. | 10 | <b>.</b> | 14  | 37 |

#### CHAPTER VI.

#### DESIGNING AND SETTING VALVES.

| 35. | Designing a plain slide-valve,  | ×2    |              | 10 | 3 <b>6</b> 33 | •3 | 30 | ÷. | 32  | 40 |
|-----|---------------------------------|-------|--------------|----|---------------|----|----|----|-----|----|
| 36. | To determine approximate solu   | tion, |              |    | 3.00          |    | *  |    |     | 41 |
| 37. | Equalizing lever,               |       |              |    |               |    |    |    |     | 43 |
| 38. | To put the engine on the centre | 9. C  |              | 1  | 8.6           |    | 2  |    |     | 45 |
| 39. | To set the valve,               | ·**   | $\mathbf{x}$ | 56 | 3.00          |    | 30 |    | 363 | 45 |

#### CHAPTER VII.

e.

#### THE STEPHENSON LINK.

| 40.  | The link,            |     | $(\mathbf{r})$ | •          |    |    | 39 |       | •  |   | 47 |
|------|----------------------|-----|----------------|------------|----|----|----|-------|----|---|----|
| 41.  | Point of suspension, |     |                |            |    |    |    |       |    |   | 48 |
| 42.  | Slip of block, ,     |     |                |            |    |    |    |       |    |   | 48 |
| 43-  | Radius of the link,  |     |                | <b>8</b> 3 | ۲  |    |    |       |    |   | 50 |
| .44. | Kinds of links, .    | 1.1 | 3.003          | •%         | 32 | 12 | 12 | 1.000 | •3 | • | 50 |

vi

#### CONTENTS.

224 IV 2

4

.

2

.

1.5

#### CHAPTER VIII.

#### THE VALVE-DIAGRAM.

| 45. | Travel of the valve,   | •                | 4      |     | 1           |       |    |  |    |        | 52 |
|-----|------------------------|------------------|--------|-----|-------------|-------|----|--|----|--------|----|
| 46. | The valve-diagram,     | 16               | 6      |     | 1           |       | 12 |  |    |        | 55 |
| 47. | Curve of centres,      | $\mathbf{x}_{i}$ |        |     | <b>.</b>    | 303   | 12 |  | 23 | 1.00   | 56 |
| 48. | To lay down the valu   | e-di             | agram, |     |             |       |    |  |    | 30.00  | 56 |
| 49- | The virtual eccentric, |                  |        | 25  |             |       | •  |  |    |        | 58 |
| 50. | Designing the gear,    | 85               |        | 30U |             | 3.00  |    |  |    |        | 58 |
| 51. | Valve-stem and eccen   | tric-            | rod,   |     | 3. <b>.</b> | 3.002 | •2 |  |    | S2003  | 58 |
| 52, | Length of link, .      | •                |        |     |             |       |    |  | 22 |        | 59 |
| 53- | The hanger, .          |                  |        | 1   |             |       |    |  |    |        | 59 |
| 54  | Link suspended at bo   | tton             | or cer | tre | of ch       | ord,  | •0 |  | 30 | 10.00  | 60 |
| 55. | Open and crossed rod   | ls,              | •      |     | 58 <b>.</b> | 10000 | •0 |  |    | 20.000 | 6τ |

#### CHAPTER IX.

#### EQUALIZING LEAD AND CUT-OFF.

| 56.  | Equalizing lead,         |        | 36      |         |                | <ul> <li>0</li> </ul> | •       |    | 3 <b>.</b>  | 166  | 63 |
|------|--------------------------|--------|---------|---------|----------------|-----------------------|---------|----|-------------|------|----|
| 57.  | Equalizing cut-off, .    | ÷.,    |         | 25      |                | 82                    |         |    | S. <b>.</b> | 0.00 | 65 |
| 58   | To lay down the motion   |        | - 12 I  |         | 102            | . 8                   | •       |    |             |      | 67 |
| 59.  | To lay down the centre   | of the | e trave | l of th | he val         | lve,                  | - 18 I. |    |             |      | 67 |
| •60. | To determine the centre  | of su  | apensi  | on of   | the b          | ange                  | · ·     |    |             |      | 68 |
| 61.  | Position of stud, .      |        |         |         | 59 <b>9</b> 00 | 15                    |         |    | <b>.</b>    | 0.00 | 68 |
| -62. | Reducing slip,           |        | 1       |         | 1.             |                       |         |    |             |      | 70 |
| 61.  | Error of the Zeuner dias | cano.  | 100     | - 52    | 93.20          | - 25                  | - 23    | 32 | 100         | 553  | 70 |

#### CHAPTER X.

#### THE GOOCH MOTION.

| -64. | The Gooch link,  |      |       | 25 | ×  | æ          | 3   |      |   | æ | 8.  | 2.9 | 75 |
|------|------------------|------|-------|----|----|------------|-----|------|---|---|-----|-----|----|
| 65,  | Movement of the  | t va | lve,  | 4  |    |            |     |      |   |   |     | •   | 76 |
| -66. | Constant lead,   | 1    |       |    | 20 |            | 14  | 1.5  |   | 1 | 1   |     | 78 |
| -67. | Radius of link,  | •    |       |    |    | 10         | 100 | 0.40 |   |   | 14  |     | 78 |
| -68. | Suspension-rod,  |      | •     |    |    |            |     |      | • |   | *   |     | 79 |
| -69. | The hanger,      |      |       |    |    |            |     |      |   |   |     |     | 80 |
| 70.  | The valve-diagra | m,   | •0    |    |    |            |     | - 22 |   |   |     | 8   | 80 |
| 71.  | To design a Goo  | ch i | motio | a, |    | 3 <b>8</b> |     |      |   |   | 3.9 | 500 | 82 |

#### CHAPTER XI.

#### THE ALLEN AND FINK MOTIONS.

| 72. | The Allen link-motion, | 38)<br>190 | ÷. | 12 | 843 | <b>#</b> 2: |  | 1.672     | 85 |
|-----|------------------------|------------|----|----|-----|-------------|--|-----------|----|
| 73. | The valve-diagram,     | 10         | 32 | 30 | -03 |             |  | <br>0.000 | 85 |

vii