

**REPORT OF THE RESULTS
OBTAINED WITH EXPERIMENTAL
FILTERS AT THE PETTACONSET
PUMPING STATION OF THE
PROVIDENCE WATER WORKS**

Published @ 2017 Trieste Publishing Pty Ltd

ISBN 9780649225927

Report of the results obtained with experimental filters at the Pettaconset pumping station of the Providence water works by Edmund B. Weston

Except for use in any review, the reproduction or utilisation of this work in whole or in part in any form by any electronic, mechanical or other means, now known or hereafter invented, including xerography, photocopying and recording, or in any information storage or retrieval system, is forbidden without the permission of the publisher, Trieste Publishing Pty Ltd, PO Box 1576 Collingwood, Victoria 3066 Australia.

All rights reserved.

Edited by Trieste Publishing Pty Ltd.
Cover @ 2017

This book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form or binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser.

www.triestepublishing.com

EDMUND B. WESTON

**REPORT OF THE RESULTS
OBTAINED WITH EXPERIMENTAL
FILTERS AT THE PETTACONSET
PUMPING STATION OF THE
PROVIDENCE WATER WORKS**

APPENDIX TO THE SEVENTEENTH ANNUAL REPORT OF THE
STATE BOARD OF HEALTH OF RHODE ISLAND,
FOR THE YEAR ENDING DEC. 31, 1894.

REPORT

OF THE

RESULTS OBTAINED

WITH

EXPERIMENTAL FILTERS

AT THE PETTACONSET PUMPING STATION OF THE
PROVIDENCE WATER WORKS.

BY EDMUND B. WESTON,

MEMBER OF THE AMERICAN SOCIETY OF CIVIL ENGINEERS.
MEMBER OF THE INSTITUTION OF CIVIL ENGINEERS OF GREAT BRITAIN.
ASSISTANT ENGINEER IN CHARGE OF WATER DEPARTMENT, PROVIDENCE, R. I.

PROVIDENCE, R. I.:

E. L. FREEMAN & SONS, STATE PRINTERS.

1896.

TO .VIMU
AMBROLIAO

TELE
74

GENERAL CONTENTS.

| | Page. |
|---|-------|
| INTRODUCTORY | 1 |
| Definition of Natural and Mechanical Filtration..... | 1 |
| Description of Filters Nos. 1 and 2..... | 2 |
| Description of Table No. 1, etc..... | 2 |
| Definition of "Effective Size" and "Uniformity Coefficient"..... | 4 |
| Table No. 1.—A comparison of the Results obtained from Filters Nos. 1 and 2, and the Experimental Morison Mechanical Filter from March 27 to October 5, 1893, including Rates of Filtration, Bacteriological Percentages of Removal (computed from cultivations of from 42 to 62 hours), Loss of Head due to the Flow of the Water through the Filters, Percentage of Colour Removed, and Quantity of Basic Sulphate of Alumina used..... | 5 |
| DESCRIPTION OF THE EXPERIMENTS THAT WERE MADE WITH THE EXPERIMENTAL MORISON MECHANICAL FILTER | 34 |
| The term Morison Mechanical Filter, an abbreviation of Experimental Morison Mechanical Filter..... | 34 |
| Description of the Experimental Morison Mechanical Filter..... | 34 |
| Standard Rate of Filtration decided upon..... | 34 |
| Alumina, an abbreviation of Basic Sulphate of Alumina..... | 34 |
| Details Investigated..... | 36 |
| Chemicals used during preliminary experiments..... | 37 |
| Theory of Mechanical Filtration..... | 37 |
| Definition of "Free Flow"..... | 37 |
| A proportional rise of water above filter-bed essential, in order to obtain a constant rate of filtration..... | 37 |
| Loss of Head due to "Free Flow," etc..... | 38 |
| Improvement in efficiency over Natural Filtration by adding Alumina..... | 38 |
| Description of the Method followed in adding the Sulphate of Alumina to the Applied Water, and the Apparatus used..... | 38 |
| Coagulant,—proportions of Alumina and Water used..... | 38 |
| Investigations relative to the decomposition of the Basic Sulphate of Alumina during filtration..... | 39 |
| Application of the Logwood and Acetic Acid test for Alum..... | 39 |
| Sensitiveness of Logwood and Acetic Acid test..... | 39 |
| Constituents of the Basic Sulphate of Alumina used..... | 39 |
| Experiments with Settling Tanks..... | 41 |
| Time that the Samples of water were Collected to which the Logwood and Acetic Acid test was applied..... | 41 |

| | |
|---|----|
| Bacteriological Work | 42 |
| Description of Tables | 47 |
| Tables showing Percentages of Removal of Water Bacteria. | |
| Table No. 2.—End Growths,—the Samples of Applied and Filtered Water were collected at the Same Hour. | 55 |
| Table No. 3.—Growths of about Ninety Hours,—the Samples of Applied and Filtered Water were collected at the Same Hour | 57 |
| Table No. 4.—End Growths,—the Samples of Filtered Water were collected from 1 to 9 times daily, One Hour or More after water commenced to flow from the filter | 59 |
| Table No. 5.—Growths of Eighty-five Hours or More and End Growths,—the Samples of Filtered Water were collected from 1 to 9 times daily One Hour or More after water commenced to flow from the filter. | 65 |
| Table No. 6.—End Growths,—the Samples of Filtered Water were collected Thirty Minutes or Less after water commenced to flow from the filter..... | 74 |
| Table No. 7.—Growths of about Ninety Hours,—the Samples of Filtered Water were collected Thirty Minutes or Less after water commenced to flow from the filter. | 76 |
| Table No. 8.—Growths of Eighty-five Hours or More and End Growths,—the Samples of Filtered Water were collected Thirty Minutes or Less after water commenced to flow from the filter | 78 |
| Table No. 9.—Summary of the Average Percentages given in tables Nos. 2, 3, 4 and 5,—the Samples of Filtered Water were collected One Hour or More after water commenced to flow from the filter. . . | 81 |
| Table No. 10.—Summary of the Average Percentages given in tables Nos. 6, 7 and 8,—the Samples of Filtered Water were collected Thirty Minutes or Less after water commenced to flow from the filter. | 83 |
| Tables for making Comparisons, relating to the Experimental Morison Mechanical Filter. | |
| Tables Nos. 11 and 15.—The number of times that Percentages of More than Two Per cent., of the Applied Water Bacteria, Appeared in the Filtered Water. Also the Percentages that the number of times are of the Total Number of Results obtained, (pages 85 and 90). | 85 |
| Tables Nos. 12, 14, 16 and 18.—The number of times that Percentages of the Applied Water Bacteria Removed, which were used in working up the Average Percentages given in tables Nos. 9 and 10, were One Per cent. and More Less than the Average Per cent. Removed. Also the Percentages that the number of times are of the Total Number of Results obtained. (pages 86, 88, 91 and 93). | 86 |
| Tables Nos. 13 and 17.—The number of times that Percentages of the Applied Water Bacteria Removed, which were used in working up the Average Percentages given in tables Nos. 9 and 10, were More than Two Per cent. Less than the Average Per cent. Removed. Also the Percentages that the number of times are of the Total Number of Results obtained. (pages 87 and 92). | 87 |

| | |
|---|-----|
| Table No. 19.—Percentages of Applied <i>Bacillus Prodigiosus</i> Removed from the water by filtration,—the Number that were found in the Applied and Filtered Water, and the length of time that they were grown..... | 95 |
| Table No. 20.—Chemical Analyses of Applied and Filtered Water..... | 105 |
| Table No. 20.—concluded.—Special Analysis of a Sample of Pawtuxet River Water giving Quantitative Constituents and Compounds..... | 107 |
| Table No. 21.—Percentages of Color Removed from the water by filtration, and the Color of the Applied and Filtered Water..... | 108 |
| Table No. 22.—For making Comparisons, computed from data derived from the Report of the State Board of Health of Massachusetts for the year 1892, relating to the filtration of water through Experimental Filters at the Experiment Station of the State Board of Health of Massachusetts at Lawrence, Massachusetts.—Giving Rates of Filtration,—Percentages of Removal,—The number of times that Percentages of One Per cent. and More, of the Applied Water Bacteria, Appeared in the Filtered Water of the different filters, the number of times that the Percentages of Applied Water Bacteria Removed were One Per cent. and More Less than the Average Per cent. Removed, and the Percentages that the number of times are of the Total Number of Results obtained. Also the Percentages that the number of times that More than Two Per cent. of the Applied Water Bacteria Appeared in the Filtered Water, are of the Total Number of Results obtained, and the Percentages that the number of times, that the Percentages of the Applied Water Bacteria Removed that were More than Two Per cent. Less than the Average Per cent. Removed, are of the Total Number of Results obtained..... | 114 |
| CONCLUSIONS..... | 118 |
| Filter-bed Steamed and Boiled..... | 119 |
| Experiments when the Temperature of the Applied Water was artificially raised..... | 119 |
| Foreign Matter in Filter and Filter-bed..... | 119 |
| Effective Cleansing of the Filter and Filter-bed with Caustic Soda..... | 120 |
| Higher Bacterial Percentage of Removal after Cleansing Filter and Filter-bed with Caustic Soda..... | 120 |
| Small quantity of Suspended Matter in Applied Water appeared to be beneficial..... | 120 |
| Experiments upon which the Efficiency of the Filter for Removing Bacteria is based..... | 121 |
| Estimate of the Cost of Operating, includes the Cost of Cleansing twice a year with Caustic Soda..... | 121 |
| Bacteriological Percentages of Removal considered were worked out from End Growths..... | 121 |
| Basic Sulphate of Alumina,—the Chemical best adapted for the Purification of Pawtuxet River Water..... | 122 |
| Quantity of Basic Sulphate of Alumina Required..... | 122 |

| | |
|--|-----|
| None of the Applied Basic Sulphate of Alumina in its original state, present in the Filtered Water..... | 122 |
| Rate in Gallons per Acre, per 24 hours, that could be efficiently filtered, and average rate during experiments..... | 123 |
| Recommended rate of filtration upon which capacity should be based..... | 123 |
| Bacteriological and Chemical purification of the water..... | 123 |
| Average Bacteriological Percentage of Removal..... | 124 |
| Comparison of Bacteriological Results obtained with the Morison Mechanical Filter, with those obtained by Natural Filtration, with Experimental Filters at Lawrence, Massachusetts. (pages 124 and 126)..... | 124 |
| Efficiency of a filter for removing bacteria should not be entirely based upon the Average Results, but the Worst Results should be duly considered..... | 125 |
| Temperature of the Applied Water in December and January..... | 128 |
| Possibility that a cheaper chemical than Caustic Soda could be used in cleansing the filter, in connection with steam..... | 129 |
| Application of Bacillus Prodigiosus to the Applied Water..... | 131 |
| Average Percentage of Removal of Bacillus Prodigiosus..... | 131 |
| Application of Cruikshank's Bacillus to the Applied Water..... | 132 |
| Reduction of Albuminoid Ammonia by Filtration..... | 133 |
| Reduction of Ready-formed Ammonia by Filtration..... | 133 |
| Sulphur trioxide (SO_3), in Pawtuxet River Water before and after adding Sulphate of Alumina, and in other waters..... | 133 |
| Filtered Water and Boilers..... | 135 |
| Color of the Applied Water Removed by Filtration..... | 135 |
| Filter-bed can be thoroughly washed..... | 137 |
| Average Time required for washing..... | 137 |
| Quantity of water required for Washing filter-bed..... | 137 |
| Quantity of water necessary to Waste after washing filter-bed..... | 137 |
| Time that Filter will run between washings..... | 137 |
| Condition of the Water in the Pawtuxet River during the experiments..... | 138 |
| Effective Stability of the Quartz and Supplementary precipitate bed..... | 138 |
| Range of the Working Head of the filter..... | 141 |
| Results equally good under all heads..... | 141 |
| Number of Bacteria in samples of filter-bed..... | 141 |
| Number of Bacteria contained in a sample of Effluent Wash-water..... | 142 |
| Loss of Head, due to the water flowing through the filter..... | 142 |
| Estimated Cost of Operating, per 1,000,000 gallons, a Morison Mechanical Filter Plant..... | 142 |
| REMOVAL OF WATER BACTERIA BY SUBSIDENCE AND FLOW..... | 142 |
| FINIS..... | 143 |
| APPENDIX..... | 145 |
| Report of Professor Thomas M. Drown, upon the analysis of a sample of Pawtuxet River Water, before and after adding one-half ($\frac{1}{2}$) grain of Sulphate of Alumina..... | 146 |
| Letters from the Hartford Steam Boiler Inspection and Insurance Co., relating to boilers..... | 149 |

| | |
|--|-----|
| Letter from Dr. C. V. Chapin, giving information relative to Mechanical Filtration, obtained by personal inquiries, inspection and correspondence..... | 152 |
| Extracts from two papers published in the Transactions of the American Society of Civil Engineers, relative to the use of Alum in the purification of water..... | 156 |
| Extracts from an article, published in the Chemical News, relative to experiments with Alum Baking Powders, etc., etc..... | 157 |
| Letter from Professor C. A. Doremus, relative to the action of purified waters upon boiler scale..... | 159 |
| Letter from the Treasurer of the Providence Dyeing, Bleaching and Calendering Co., relative to experience with filtered water in boilers and wrought iron pipes..... | 160 |
| Table A.—The number of grains, per gallon, of "Alumina" and "Sulphuric Acid," which are contained in 146 Mineral Springs of the United States..... | 161 |
| Table B.—The number of grains, per gallon, of "Alumina" and "Sulphuric Acid," which are contained in some Natural Waters in Massachusetts..... | 171 |
| Table C.—The Number of Times during Fifteen Winters, that Periods occurred of One day and More, when the Daily Mean Temperature was 32° and Less at Providence, R. I..... | 172 |
| Table D.—Normal Mean January Temperature of a number of European cities and at Providence, R. I..... | 173 |
| Table E.—The Number of Times and the Number of Days in each Period, during each Winter from 1879 to 1893, that the Hope Reservoir of the Providence Water Works was Frozen Over. Also the Date that the Reservoir was Frozen Over the First Time during each Winter, and the Last Time that Ice was visible, and the Total Number of Days that the Daily Mean Temperature of the air was 32° and Less..... | 174 |
| Estimates of the Cost of Mechanical Filtration..... | 175 |
| Estimates of the Cost of Natural Filtration..... | 178 |
| Summary of the Estimates of cost, of Mechanical and Natural Filtration..... | 181 |